

Locklin Series

## **BULLET LIGHT**

GUTTER MOUNT POWER BASE - ADJUSTABLE KNUCKLE -LED MODULE - BULLET LIGHT SHROUD

#### LIGHT ARCHITECTURAL FEATURES OR LANDSCAPING FROM ABOVE

402-02BSBK



Perfect for illuminating rooflines and dormers, this uplight combines Nightscaping's patent pending Gutter Mount power base with wireless adjustability. Light architectural features or landscaping from above.

### Patented Modular Design:

Utilizes Locklin's Through Power Technology, the Twist-lock wireless system for secure, tool-free assembly. Mounts directly to fascia boards or gutters using Nightscaping's Gutter Mount.

#### PRODUCT DETAILS:

#### **Adjustable Color Temperature:**

Push-button togale between 2700K and 3000K (Hold 5 seconds to switch)

#### **Adjustable Lumen Output:**

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

#### Lumen Output (2700K)\*:

- 3W 170 lm
- 5W 292 lm
- 7W 399 lm

#### Lumen Output (3000K)\*:

- 3W 180 lm
- 5W 310 lm
- 7W 425 lm

#### Adjustable Knuckle:

Push-button adjustability for full aiming flexibility from aboveideal for architectural uplighting, gutter-mounted installs, or secondstory lighting.

#### Optics:

- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° spread achieved by removing optics.
- Color-coded lenses for easy identification.

#### Glare Control:

Includes optional Honeycomb Louver.

#### Power Base Wire Lead:

3' lead included with Gutter Mount Power Base.

#### Shroud:

The Bullet Light Shroud delivers precise uplighting with a tapered design that feathers light forward while shielding glare from behind.

#### **Certifications:**

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC













<sup>\*</sup>Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal



# **BULLET LIGHT**

GUTTER MOUNT POWER BASE - ADJUSTABLE KNUCKLE -LED MODULE - BULLET LIGHT SHROUD

