



Locklin Series

BULLET LIGHT

SURFACE MOUNT POWER BASE- FIXED KNUCKLE -
LED MODULE - BULLET LIGHT SHROUD

CLEAN ARCHITECTURAL UPLIGHTING

401-01BSBK



Designed for **clean architectural uplighting**, this fixture delivers precise beam direction from a fixed position. Mount to any hardscape surface or walls, its compact form and Twist-lock tool-free assembly make it a smart, set-it-and-forget-it solution.

Patented Modular Design:

Assembled using Locklin's Through Power Technology and Twist-lock system, this modular fixture snaps together wire-free with gold-plated connectors for corrosion-free, tool-free assembly. Designed for mounting to patios, walls, and other flat hardscape surfaces.

PRODUCT DETAILS

Adjustable Color Temperature:

Push-button toggle between 2700K and 3000K
(Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

Lumen Output (3000K)*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

Fixed Knuckle:

Slimline, low-profile fixed knuckle delivers consistent beam direction without rotation or tilt—ideal for static accent lighting on walls or pillars.

Optics:

- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° spread achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honeycomb Louver.

Power Base Wire Lead:

25' lead included with Surface Mount Power Base

Shroud:

The Bullet Light Shroud delivers precise uplighting with a tapered design that feathers light forward while shielding glare from behind.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal





Locklin Series

BULLET LIGHT

SURFACE MOUNT POWER BASE- FIXED KNUCKLE -
LED MODULE - BULLET LIGHT SHROUD

