

WASH LIGHT

ABS STAKE MOUNT POWER BASE - ADJUSTABLE KNUCKLE -LED MODULE - WASH LIGHT SHROUD

VARIABLE UPLIGHTING COVERAGE

403-02WSBK



This wide-beam fixture brings smooth, ambient wash lighting to walls and small trees. The adjustable knuckle delivers variable uplighting coverage for small trees, garden art, and low architectural features that are situated in mulch and garden beds away from grass.

Patented Modular Design:

Modular landscape wash-light built with Locklin's Twist-lock snap-in system, Through Power Technology, and gold-plated connectors, designed to create a uniform lighting effect across landscape and architectural features. The ABS Ground Stake Power Base provides strong in-ground anchoring.

PRODUCT DETAILS

Adjustable Color Temperature:

Push-button togale between 2700K and 3000K (Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

• Press once: 3W • Press twice: 5W • Press three times: 7W

Lumen Output (2700K)*:

- 3W 170 lm
- 5W 292 lm
- 7W 399 lm

Lumen Output (3000K)*:

- 3W 180 lm
- 5W 310 lm
- 7W 425 lm

Adjustable Knuckle:

360° rotation and tilt with pushbutton locking allow precise aiming of the wide wash beam in landscape applications.

Optics:

- Integrated linear spread lens
- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honevcomb Louver.

Power Base Wire Lead:

25' lead included with ABS Stake Mount Power Base.

Shroud:

The Wash Light Shroud delivers soft, ambient illumination across plantings. walls, and walkways with an integrated linear lens for smooth, even light.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94 • TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC













^{*}Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal



WASH LIGHT

LED MODULE - WASH LIGHT SHROUD Locklin Series ø75.5 [ø2.97 **"**] Ø49.1 [ø1.93 **"**] Ø44.0 [ø1.73 **"**]