

Locklin Series

WASH LIGHT

GUTTER MOUNT POWER BASE- ADJUSTABLE KNUCKLE - LED MODULE - WASH LIGHT SHROUD

AMBIENT WASH LIGHTING TO DORMERS AND UPPER ARCHITECTURAL ELEMENTS

402-02WSBK



This wide-beam fixture brings smooth, ambient wash lighting to dormers and upper architectural elements that are within a close proximity to gutter mounting locations. The built-in, linear spread, optical lens provides an even transmission of light with smooth fall off on the edges making it ideal for illuminating light colored and smooth surfaced architecture.

Patented Modular Design:

Combines the Locklin Series' Gutter Mount system with Twist-lock wireless connections and Through Power Technology for zero-tool installation to soffits, fascia boards, or gutters.

PRODUCT DETAILS

Adjustable Color Temperature:

Push-button togale between 2700K and 3000K (Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W • Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W 170 lm
- 5W 292 lm
- 7W 399 lm

Lumen Output (3000K)*:

- 3W 180 lm
- 5W 310 lm
- 7W 425 lm

Adjustable Knuckle:

Push-button adjustable for full tilt and rotational aiming—perfect for soft uplighting from elevated architectural positions.

Optics:

- Integrated linear spread lens
- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honevcomb Louver.

Power Base Wire Lead:

3' lead included with Gutter Mount Power Base.

Shroud:

The Wash Light Shroud delivers soft, ambient illumination across plantings, walls, and walkways with an integrated linear lens for smooth, even light.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94 • TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



















GUTTER MOUNT POWER BASE- ADJUSTABLE KNUCKLE - LED MODULE - WASH LIGHT SHROUD

