



Locklin Series

BULLET LIGHT

GUTTER MOUNT POWER BASE - ADJUSTABLE KNUCKLE -
LED MODULE - BULLET LIGHT SHROUD

LIGHT ARCHITECTURAL FEATURES OR LANDSCAPING FROM ABOVE

402-02BSBK



Perfect for illuminating rooflines and dormers, this uplight combines Nightscaping's patent pending Gutter Mount power base with wireless adjustability. **Light architectural features or landscaping from above.**

Patented Modular Design:

Utilizes Locklin's Through Power Technology, the Twist-lock wireless system for secure, tool-free assembly. Mounts directly to fascia boards or gutters using Nightscaping's Gutter Mount.

PRODUCT DETAILS

Warranty:

10 Year Warranty

Adjustable Color Temperature:

Push-button toggle between
2700K and 3000K
(Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

Lumen Output (3000K)*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

Adjustable Knuckle:

Push-button adjustability for full aiming flexibility from above—ideal for architectural uplighting, gutter-mounted installs, or second-story lighting.

Optics:

- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° spread achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional
Honeycomb Louver.

Power Base Wire Lead:

3' lead included with Gutter Mount
Power Base.

Shroud:

The Bullet Light Shroud delivers precise uplighting with a tapered design that feathers light forward while shielding glare from behind.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal





Locklin Series

BULLET LIGHT

GUTTER MOUNT POWER BASE - ADJUSTABLE KNUCKLE -
LED MODULE - BULLET LIGHT SHROUD

