



Locklin Series

TREE LIGHT

TREE LIGHT MOUNT POWER BASE - ADJUSTABLE KNUCKLE - LED MODULE - EXTENDED SHROUD

PRECISE, LOW-GLARE ILLUMINATION

400-02TSBK



The perfect downlight built from Nightscaping's modular components. Includes the Tree Light Mount Power Base, Adjustable Knuckle, Adjustable LED Module, and Tree Light Shroud for **precise, low-glare illumination** from the canopy above.

Patented Modular Design:

Built on Nightscaping's Twist-lock system using Locklin's Through Power Technology, the Tree Light assembles entirely without tools. Each component—Power Base, Knuckle, LED Module, and Shroud—connects via gold-plated aerospace-certified pins to deliver a corrosion-proof, vibration-resistant lighting solution made for elevated installs.

PRODUCT DETAILS

Warranty:

10 Year Warranty

Adjustable Color Temperature:

Push-button toggle between 2700K and 3000K (Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

Lumen Output (3000K)*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

Adjustable Knuckle:

Adjustable knuckle with 360° rotation and vertical tilt.

Push-button locking for tool-free aiming from the canopy.

Optics:

- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honeycomb Louver.

Power Base Wire Lead:

50' detachable wire lead included with Tree Mount Power Base

Shroud:

Extended Tree Light Shroud designed specifically for elevated, glare-free downlighting and moonlighting effects.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal



TREE LIGHT

TREE LIGHT MOUNT POWER BASE - ADJUSTABLE KNUCKLE -
LED MODULE - EXTENDED SHROUD

