



Locklin Series

WASH LIGHT

SURFACE MOUNT POWER BASE - ADJUSTABLE KNUCKLE
- LED MODULE - WASH LIGHT SHROUD

FLEXIBLE LIGHTING

401-02WSBK



This wide-beam fixture brings smooth, ambient wash lighting to walls and small trees. The adjustable knuckle delivers more flexibility for lighting garden art, shrubs, and low trees, along with low architectural features that are isolated in hardscape or solid surface areas where a Ground Stake cannot be used.

Patented Modular Design:

Built on the Locklin Series' modular Twist-lock platform with Through Power Technology, this fixture mounts to solid surfaces using a tool-free, snap-fit system with gold-plated connectors.

PRODUCT DETAILS

Warranty:

10 Year Warranty

Adjustable Color Temperature:

Push-button toggle between 2700K and 3000K (Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

Lumen Output (3000K)*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

Adjustable Knuckle:

360° rotation and vertical tilt with push-button locking lets you direct wide-area lighting exactly where it's needed.

Optics:

- Integrated linear spread lens
- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honeycomb Louver.

Power Base Wire Lead:

25' lead included with Surface Mount Power Base.

Shroud:

The Wash Light Shroud delivers soft, ambient illumination across plantings, walls, and walkways with an integrated linear lens for smooth, even light.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal



WASH LIGHT

SURFACE MOUNT POWER BASE - ADJUSTABLE KNUCKLE
- LED MODULE - WASH LIGHT SHROUD

