



Locklin Series

# WASH LIGHT

TRIDENT STAKE MOUNT POWER BASE - FIXED KNUCKLE -  
LED MODULE - WASH LIGHT SHROUD

## CONSISTENT UPLIGHTING COVERAGE

404-01WSBK



This wide-beam fixture brings smooth, ambient wash lighting to walls and small trees. The fixed knuckle delivers consistent uplighting coverage for columns, garden art, and low architectural features that are situated in mulch and garden beds away from grass.

### Patented Modular Design:

Engineered with Locklin's quick-connect system and Through Power Technology and secured with a three-rod Trident Stake for extra stability in tough, unforgiving soils.

## PRODUCT DETAILS

### Warranty:

10 Year Warranty

### Adjustable Color Temperature:

Push-button toggle between 2700K and 3000K (Hold 5 seconds to switch)

### Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

### Lumen Output (2700K)\*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

### Lumen Output (3000K)\*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

### Fixed Knuckle:

Locks beam direction in place —ideal for long-term, consistent wash lighting of facades, low walls, or plant groupings.

### Optics:

- Integrated linear spread lens
- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

### Glare Control:

Includes optional Honeycomb Louver.

### Power Base Wire Lead:

25' lead included with Trident Stake Mount Power Base.

### Shroud:

The Wash Light Shroud delivers soft, ambient illumination across plantings, walls, and walkways with an integrated linear lens for smooth, even light.

### Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



\*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal

# WASH LIGHT

TRIDENT STAKE MOUNT POWER BASE - FIXED KNUCKLE -  
LED MODULE - WASH LIGHT SHROUD

