



Locklin Series

CAN LIGHT

CAN LIGHT MOUNT POWER BASE - LED MODULE -
CAN LIGHT SHROUD

FLUSH SOLUTION FOR DOWNLIGHTING

405-01CSBK / 405-01CSWT



The Can Light creates a clean, flush solution for downlighting from soffits, overhanging eaves and patio covers with ease.

Patented Modular Design:

The Locklin Can Light is built using Nightscaping's Twist-Lock system and Through Power Technology with wireless, gold-plated connectors for tool-free installation. Designed to be used for outdoor soffits, architectural overhangs, and ceilings inside patio structures.

Note: Cutout hole size 2 5/8"

PRODUCT DETAILS

Warranty:

10 Year Warranty

Flush-Mount Form Factor:

The integrated Can Light Shroud is pre-installed within the housing to deliver subtle, directional light without exposing hardware or creating glare. No visible fasteners, no tilt — just a clean architectural finish.

Adjustable Color Temperature:

Push-button toggle between 2700K and 3000K
(Hold 5 seconds to switch)

Adjustable Lumen Output:

Push-button control:

- Press once: 3W
- Press twice: 5W
- Press three times: 7W

Lumen Output (2700K)*:

- 3W - 170 lm
- 5W - 292 lm
- 7W - 399 lm

Lumen Output (3000K)*:

- 3W - 180 lm
- 5W - 310 lm
- 7W - 425 lm

Optics:

- 60° optic pre-installed.
- 36° optic included.
- Optional 15° and 7° sold separately.
- 120° beam achieved by removing optics.
- Color-coded lenses for easy identification.

Glare Control:

Includes optional Honeycomb Louver.

Additional Features:

Can Light masking paint plug included with white Can Light to assist with custom painting shroud.

Power Base Wire Lead:

3' lead pre-installed in the Can Light Power Base

Shroud:

Low-profile shroud that installs flush into ceilings for clean, discreet downlighting.

Certifications:

- ETL Listed
- IP68 Rated
- CRI: 93.4
- TM-30 RF: 94
- TM-30 RG: 99
- Power Factor: 0.893 @ 12VAC



*Tested at 12 volts. Lumen output will increase as voltage increases. 12v input optimal





Locklin Series

CAN LIGHT

CAN LIGHT MOUNT POWER BASE - LED MODULE -
CAN LIGHT SHROUD

